

PRESS RELEASE

Cut 9.5m With Only 150hp With the All New EXTR∆ 395 from Vicon.

26.08.2013, Kerteminde, Denmark



Vicon EXTR∆ 395

The new EXTR∆ 395 provides efficient performance with its 9.5m working width paired with a low weight design. It is purpose build to low operating costs in terms of power and fuel consumption, with power requirements starting at only 150 hp.

Vicon expands its range of low weight butterfly combinations by adding the new EXTR Δ 395 to the existing 8.75m version EXTR Δ 390. The new mower combination consists of 2 x 3.6m wide mowing units, adding up to a working width of 9.5m

High Output Mower

Low weight doesn't mean low spec with the EXTR Δ 395. It is designed to match the needs of large-scale mowing and is packed with features to meet these demands. The centre suspended mowing units in combination with the three-bladed discs offers an unmatched





cutting performance. With three blades per disc each knife has a third less load compared to two-knifed discs. With a third less load on each knife they will last and cut for longer period, providing longer period with neat, cleanly cut stubble.

Low Weight Promotes Low Fuel Consumption

The new EXTR Δ 395 is an eco-friendly, energy saving solution able to work on tractors with as little as 150hp. The low weight of only 1500kg together with the ideal weight distribution that butterfly combinations offer gives the optimum combination of low power requirements, low weight and high efficiency.



Centre Suspended Mowing Units

The mowing units are centre suspended via a suspension spring, to give an even weight distribution across the complete mower width. Faster and more precise adaptation to ground contours is also achieved because of the centre suspended design. The benefit is less skid wear and optimum protection of the stubble.

For greater versatility, the EXTR Δ 395 can be adjusted for optimal operation according to different circumstances such as field contours or working width of the front mounted mower. To ensure optimal overlap between front and rear units, the mowing units can be mounted in two positions on the suspension arm.

The Vicon BreakBack solution protects the cutterbar from foreign obstacles, and automatically returns the mowing unit into work position.

The EXTR Δ 395 will stay below 4m transport height. For transport the mower folds into a compact position above 90°, distributing weight evenly for better stability during high speed road transport.





Vicon EXTR∆ 395, Specifications in Brief:

	EXTR∆ 395
Working Width	9.50m
Weight	1500kg
Power Requirements	110kW/150 hp
Number of discs per mowing unit	10 triangular discs

Download high resolution images of the EXTR∆ 395 here:

Download image of EXTRA 395



Download image of EXTRA 395



Download image of EXTRA 395 in transport



Download image of two mounting options



Download image of suspension



Download detail image of NonStop BreakBack





Kverneland Group is a leading international company developing, producing and distributing agricultural machinery and services. Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package aimed at the professional farming community, covering the areas of soil preparation, seeding, forage and bale equipment, spreading, spraying and electronic solutions for agricultural tractors and machinery. For more information on Kverneland Group visit www.kvernelandgroup.com

-- END --

For more information, contact:

Stefan Zimmermann Product Manager, Vicon Disc and Drum Mowers

Phone: + 49 1520 91 96 745

E-Mail: stefan.zimmermann@kvernelandgroup.com

Vicon and iM FARMING Online:



Visit our web site www.vicon.eu



Like us on facebook www.facebook.com/KvernelandGroup www.facebook.com/iMFarming



Watch us on YouTube www.youtube.com/kvernelandgrp



Follow us on Twitter @KvernelandGroup @iM_Farming

