



PRESS RELEASE

Kverneland Introduces new 11,2 m Trailed Rotary Tedder

23.08.2016, Kerteminde, Denmark

Kverneland 85112 C, new trailed maintenance free tedder with 11.2m working width.

Kverneland launches its new 85112 C, an 11,2 m trailed rotary tedder that delivers high performance combined compact and modern design.



High efficiency with 11.2m working width in combination of low tractor power requirement

11.2m Working Width

The 85112 C will exchange the model 80110 C into the next generation. 11.2 m working width together with 10 rotors secure perfect results in all crop conditions. Thanks to the compact folding, the machine is shorter than the previous model.

Easy to use

The basic execution requires two double acting outlets, for transport folding and hydraulic boarder tedding. Optional a hydraulic headland management is as well available. This can be controlled via a rope. The comfort kit includes a handheld to preselect between normal transport folding, headland management and lifting & lowering of just the transport carrier. The comfort kit secures a clean machine without rope.

The new tandem land wheel can be assembled to operate also under difficult conditions.

Kverneland Group Kerteminde AS, Taarupstrandvej 25, DK-5300 Kerteminde, Denmark





This and other options result in the possibility to customize the machine perfectly to customer needs.

Minimum Maintenance Promotes High Uptime

The biggest improvement of Maintenance free tedding is as well transferred into this new model. The machine is in Season fully maintenance free. No time is wasted for greasing. This is realized thanks to the already known maintenance free gearboxes. Joints in the driveline including bearings are free of maintenance as well. The hinges are as well maintenance free.

Compact construction

The new 85112 C is built in a short and compact design. High maneuverability on the road and as well in the headland are the result. The transport wheels are lifted during work, so they don't create additional tracks in the field. On the road the wide transport carrier supports high stability of the machine.



Compact transport dimensions with a transport length of only 4,29 m

Number of Characters (with spaces) in Text and Main Heading: 331





Kverneland 85112 C - Specifications in Brief:

	Kverneland 85112 C
Working Width	11.2m
Transport Width	2.95m
Transport Height	3.94m
Weight	2225kg
Rotors/Arms pr. Rotor	10/6

Download high-resolution images of Kverneland 85112 C here:

Download Kverneland 85112C image 01

Text: Kverneland 85112 C, High efficiency with 11.2m working width in combination of low tractor power requirement

Download Kverneland 85112C image 02

Text: The new Kverneland 85112 C provides compact transport dimensions with a transport length of only 4,29 m

Kverneland Group is a leading international company developing, producing and distributing agricultural machinery and services. Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package aimed at the professional farming community, covering the areas of soil preparation, seeding, forage and bale equipment, spreading, spraying and electronic solutions for agricultural tractors and machinery. For more information on Kverneland Group visit www.kvernelandgroup.com

-- END --

For Details, Contact:

Sebastian Hagemann

Product Manager, Hay Tools and Smart Farming

Kverneland Group Gottmadingen

Tel. +49 173 56 53 991

Email: sebastian.hagemann@kvernelandgroup.com

Visit our Web Site Like us on Facebook Follow us on Twitter Watch us on YouTube









KvernelandGroup iMFarming



@KvernelandGroup @iM Farming

